

ARCHITECTURAL LINE IP54

Profil Z208

Optik

<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
10° Narrow Beam Frosted	30° Frosted	90° Frosted	85° Asymmetric Frosted
Transmission 82% 20,2 mm	Transmission 85%	Transmission 90%	Transmission 90%
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
120° Cover White	120° Cover Frosted	120° Cover Flat White	120° Cover Flat Frosted
Transmission 75%	Transmission 92%	Transmission 70%	Transmission 87%

Modul L14-UHD

CRI >90

Endkappe Cinch

Farbtemperatur
Lichtstrom
Leistung

*W/Modul @ 24Vdc
Modullänge 140mm

Farbtemperatur (CRI>90)

2.400 K 2.700 K 3.000 K 4.000 K 5.000 K

Leistung

1W / Modul*

1,5W / Modul*

1,9W / Modul*

2,5W / Modul*

<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
95 lm	100 lm	103 lm	114 lm	114 lm
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
145 lm	153 lm	158 lm	175 lm	175 lm
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
196 lm	206 lm	213 lm	235 lm	235 lm
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
246 lm	260 lm	268 lm	296 lm	296 lm

Länge

(Maximale Länge 3.400mm)

Schutzart

IP54 CE (Cinch mit Protection Plug)

Einbausituation

Max. Umgebungs-
temperatur

Fixing Plates
Montageplatten

<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
LED FIXING PLATE ECS 0° 88166859	LED Z161 FIXING PLATE ECS 0° 88712147	LED FIXING PLATE ECS 15° 88167372	LED FIXING PLATE ECS 30° 88167373	LED FIXING PLATE ECS 45° 88167374	LED FIXING PLATE ECS 60° 88167375
LED FIXING PLATE METAL 0° 88167376	LED FIXING PLATE METAL 0° Magnetic 88167382	LED METAL ANGLE ECS 30° 88167378	LED METAL ANGLE ECS 45° 88167379	LED FIXING PLATE METAL - adjustable 88167384	LED MAGNETIC PLATE METAL - adjustable 88167385

LED Treiber

SCHALTBAR

- CONVERTER 35W
24V IP20
LTP-1077-V01
- CONVERTER 60W
24V IP20
LTP-1062-V0
- CONVERTER 100W
24V IP20
LTP-1063-V01
- CONVERTER 120W
24V IP67
LTP-1078-V01
- CONVERTER 200W
24V IP20
LTP-1046-V01

DIMMBAR DALI

- CONVERTER SwitchDim
35W 24V IP20
LTP-1098-V01
- CONVERTER SwitchDim
60W 24V IP20
LTP-1097-V01
- CONVERTER SwitchDim
100W 24V IP20
LTP-1096-V01
- CONVERTER SwitchDim
150W 24V IP20
LTP-1059-V01

DIMMBAR PWM

- CONVERTER PWM 40W
24V IP67
LTP-1084-V01
- CONVERTER PWM 120W
24V IP67
LTP-1048-V01

Zubehör

- | | | | |
|---|--|--|--|
| <input type="checkbox"/> LED Feeder straight
CINCH 3000 89601602 | <input type="checkbox"/> LED Bridge straight
CINCH 120 89601604 | <input type="checkbox"/> LED Bridge CINCH
direct connector 89601606 | <input type="checkbox"/> STRAIN RELIEF
CINCH PLUG 90° 24166456 |
| <input type="checkbox"/> LED Feeder angled
CINCH 4000 89601603 | <input type="checkbox"/> LED Bridge straight
CINCH 250 89601607 | <input type="checkbox"/> LED PROTECTION PLUG
CINCH black 88167416 | <input type="checkbox"/> STRAIN RELIEF CINCH
PLUG STRAIGHT 24166457 |
| <input type="checkbox"/> LED Feeder straight
CINCH 5000 89601611 | <input type="checkbox"/> LED Bridge angled
CINCH 50 89601610 | <input type="checkbox"/> LED SEALING RING
CINCH black 88167417 | |

Weiteres Zubehör finden Sie online unter www.lumitech.com